



Westfalen

Product sheet ISCEON® M079 (R-422A)

Product name	ISCEON® M079 (R-422A)
Physical state	liquefied under pressure
Chemical sign	CHF ₂ CF ₃ + CF ₃ CH ₂ F + CH(CH ₃) ₂
Chemical designation	R-422A
Purity	99,5 %
Standard	DIN 8960
Properties	see safety data sheet
Shoulder color	yellow green (RAL 6018)

Components	
R-125 (Pentafluoroethane)	85,1 wt%
R-134a (1,1,1,2-Tetrafluoroethane)	11,5 wt%
R-600a (Isobutane)	3,4 wt%

Minor components	Maximum values
organic substances	0,5 wt%
Moisture	25,0 wt. ppm
high-boiling residues	50,0 wt. ppm
non-condensable gases	1,5 vol.%

Name	Material number	Bottle type	Bottle container volume	Vapour/filling pressure	Content	Valve	Properties
Refrig. ISCEON M079 R 422 A T12 RCyl.	S06690112	steel	12,0 l		10,0 kg		
Refrig. ISCEON M079 R 422 A T27 RCyl.	S06690127	steel	27,0 l		23,0 kg		
Refrig. ISCEON M079 R 422 A T61 RCyl:53	S06690161	steel	61,0 l		53,0 kg		

Vapour pressure corresponds to 293.15 K (20°C).



Typical applications

- as a refrigerant
- in deep freezing

Physical data

operating figures	Safety group according to DIN EN 378	A1
	Global warming potential (GWP ₁₀₀)	3143
	Molar mass	113,6 g mol ⁻¹
	Flammability (LFL)	- kg m ⁻³
	ozone depletion potential	0
	practical threshold value	0,29 kg m ⁻³
Liquid State	Boiling temperature at the bubble point	226,65 (-46,5) K (°C)
Critical Point	Temperature	344,85 (71,7) K (°C)
	density	538,5 kg m ⁻³
	Pressure	37,5 bar

All mentioned data, values and notes correspond to actual state of knowledge on the date of printing. They make no claim to be correct or complete and therefore do not release the user from his obligation to check them.

Current state 17.01.2020